REVISIONS			
NO	DESCRIPTION	APPROVED	DATE



Impedance.....50Ω
Frequency range.....DC ~ 4GHz
V.S.W.R.....N/A
Dielectric withstanding
- Voltage(at sea level).....1500Vrms.50Hz
- Working voltage(at sea level).....≤500Vrms.50Hz
Insulation resistance.....≥5.10^{3}MΩ
Center contact resistance.....≤1.5MΩ
Out contact resistance.....≥1MΩ
Temperature range.....-65℃ ~ +165℃
Temperature shock.....MIL-STD202,Method107,ConditionB
Moisture resistance.....MIL-STD202,Method106
Corrosion.....Saltspray Test acc.to MIL-STD-202, Method101,ConditionB
Vibration.....MIL-STD202,Method204,ConditionB
Shock.....MIL-STD202,Method213,ConditionG
Couling nut torque
- Recommended torque....7Ncm/28Ncm/0.6in.lbs.~2.5in.-lbs
Coupling retention force.....≥450N/101.2lbs.
Contact captivation.....≥27N/6.1lbs.
Durability(Matings).....≥500

Connector parts	Material	Plating
Bodys	Brass	Nickel
Cente contact	Brass	Gold
Insulator	PTFE	White

TOL.UNLESS NOTED
X = ±0.1
X.X = ±0.05
X.XX = ±0.01

DATE	
DRAWN BY	
DESINGNED BY	
CHECKED BY	
APPD.BY	
SCALE 1 : 1	UNIT mm

RFAC Solutions www.rfacsolutions.com

TITLE
BNC STRAIGHT PLUG
(RG-174. 188. 316)

DRAWING NO
R360-005-000

SHEET 1 OF 1