


Series 195 Low-Loss Coaxial Cable

Type : RFAC-195 (DW-195)

Document	DW-195
Issue Date	Jan.17 th .2006
	Page 2



Cable Ordering Information

Part Number	MI Number	NEC / CSA Listing	Remark
DW-195	TU-1311	none	

Characteristics

Material	Detail	inches	mm
Inner Conductor	Bare Copper	0.0374	0.95
Dielectric	Foamed Polyethylene	0.110	2.79
1 st Outer Conductor	Sealed AP Tape	0.116	2.95
2 nd Outer Conductor	92% Tinned Copper Braid	0.139	3.53
3 rd Outer Conductor	---	---	---
4 th Outer Conductor	---	---	---
Floodant	---	---	---
Jacket	PE, Black	0.195	4.95
Twisted Pairs	---	---	---
Messenger	---	---	---
Mechanical Specifications			
Minimum Bend Radius		0.5	12.7
Product Weight	(less reel)	21.5 lbs/kft	32 kg/km

Customers are reminded that they are SOLELY responsible for confirming that all products are properly installed and used in accordance with all applicable codes and regulations.

uncontrolled copy

All Rights Reserved,
Specifications subject to change without notice

Series 195 Low-Loss Coaxial Cable

Type : RFAC-195 (DW-195)

Document	DW-195
Issue Date	Jan.17 th .2006
Page	2 of 2

Electrical Specifications		
Characteristic Impedance, Ω	50 \pm 3	
Velocity of Propagation, %	82	
Capacitance, Nominal	24.3 pF/ft	79.7 pF/m
DC Resistance	Ω / kft	Ω / km
Inner Conductor	7.6	24.94
Outer Conductor	4.9	16.08
Loop	12.5	41.02

Attenuation, Nominal @ 68 °F (20 °C)		
Frequency, MHz	dB / 100 ft	dB / 100 m
150	4.4	14.6
220	5.4	17.7
450	7.8	25.5
900	11.1	36.5
1500	14.5	47.7
1800	16.0	52.5
2000	16.9	55.4
2500	19.0	62.4

Notes:

Customers are reminded that they are SOLELY responsible for confirming that all products are properly installed and used in accordance with all applicable codes and regulations.

uncontrolled copy
 All Rights Reserved,
 Specifications subject to change without notice