



REVISIONS			
NO	DESCRIPTION	APPROVED	DATE



Impedance.....50Ω
 Frequency range.....DC ~ 4GHz
 V.S.W.R.....N/A
 Dielectric withstanding
 - Voltage(at sea level).....750Vrms.50Hz
 - Working voltage(at sea level).....≤250Vrms.50Hz
 Insulation resistance.....≥10⁴ MΩ
 Center contact resistance.....≤6MΩ
 Out contact resistance.....≥1MΩ
 Temperature range.....-65°C ~ +165°C
 Temperature shock.....MIL-STD202,Method107,ConditionC
 Moisture resistance.....MIL-STD202,Method106
 Corrosion.....Saltspray Test acc.to MIL-STD-202,
 Method101,ConditionB
 Vibration.....MIL-STD202,Method204,ConditionD
 Engagementforce.....8N-63N/1.8lbs.-14.2lbs.
 Diengagementforce.....8N-63N/1.8lbs.-14.2lbs.
 Contact captivation.....≥18N/4.0lbs.
 Durability(Matings).....≥500

Mounting hole



Connector parts	Material	Plating
Bodys	Brass	Gold
Center contact	Brass	Gold
Insulator	PTFE	White

TOL.UNLESS NOTED
 X = ±0.1
 X.X = ±0.05
 X.XX = ±0.01

DATE		RFAC Solutions rfacsolutions.com
DRAWN BY		
DESIGNED BY		TITLE
CHECKED BY		SMB BULKHEAD JACK
APPD.BY		DRAWING NO
SCALE 1 : 1	UNIT mm	R340-017-000
		SHEET 1 OF 1